



- High saturation characteristic core for large saturation current and low loss.
- Closed magnetic circuit design reduces leakage flux.
- High precision DCR.
- Halogen Free & ROHS compliant.
- Operating temperature: -40 to +125 °C

- AI Servers, Data Centers, GPU/AI Accelerators.
- Desktop Motherboards, CPU/GPU Power Delivery.
- Multi-phase VRM, High-current DC-DC Converters.
- Networking Equipment, Communication Infrastructure.



MDVR090610	9.6 max	6.4 max	10.4 max	3.2 typ	3.2 typ	1.50 typ	1.00 typ
MDVR10056	10.2 max	5.0 max	6.0 max	4.0±0.3	1.4±0.5	1.25 typ	1.20 typ
MDVR120612	12.0 max	6.0 max	12.2 max	2.55 typ	2.55 typ	1.63 typ	1.27 typ



MDVR090610	10.1	3.9	5.8	1.0	3.8	3.8
MDVR10056	10.4	4.4	6.9	1.0	4.5	1.9
MDVR120612	12.2	4.39	7.94	0.85	3.05	3.05

				Satura on	(mΩ)	(mΩ)
MDVR090610-R15L	150	±15%	71	65	0.125	0.45

				Satura on	(mΩ)	(mΩ)
MDVR10056F-R12K	120	±10%	40	54	0.29	0.70


				Satura on	(mΩ)	(mΩ)
MDVR120612-R10K	100	±10%	75	130	0.125	0.37

△

:

Marking	Printing (Inductance)
---------	-----------------------

:



090610	330±1.0	100±1.0	13.2±0.5	24.5±0.2	450
10056	330±1.0	100±1.0	13.2±0.5	24.5±0.2	800
120612	330±1.0	100±1.0	13.2±0.5	24.5±0.2	300

:

•

•

•

•

•

•

•

•