

SCM Series

SMD Common Mode Inductor

Size 6033




FEATURES

- High current capability up to 400 mA
- Rated voltage: 80 VDC (42 VAC)
- Flammability corresponding to UL 94 V-0
- Operating temperature -40~+125 °C
- Quantity:2000pcs


APPLICATIONS

- USB/CAN/FireWire etc.
- Signal and sensor lines
- Power supply systems
- Suppression of common mode noise


Dimensions: [mm]



Schematic:



Land Pattern: [mm]









Electrical Properties:


	(μH)		(Ω)			(Ω)	
SCM6033-110Y	11	+50%/-30%	0.18	0.3	80	800	250
SCM6033-220Y	22	+50%/-30%	0.23	0.3	80	1500	250
SCM6033-330Y	33	+50%/-30%	0.27	0.3	80	2000	250
SCM6033-510Y	51	+50%/-30%	0.32	0.4	80	2500	250
SCM6033-101Y	100	+50%/-30%	0.58	0.3	80	4000	250
SCM6033-471Y	470	+50%/-30%	0.35	0.4	80	2200	250

Temperature Rise Current: The actual value of DC current when the temperature rise is $\Delta T=40^{\circ}\text{C}$

Typical Electrical Characteristics:




Soldering Reflow:



Preheat condition: 150 ~200 °C / 60~180 sec.
 Allowed time above 217 °C : 60~150 sec.
 Max temperature: 260 °C .
 Max time at max temperature: 10 sec.

Packaging Information:

Tape Dimension :




Series	A0 (mm)	B0 (mm)	D (mm)	P0 (mm)	P1 (mm)	W (mm)	K0 (mm)	E (mm)	T (mm)
SCM6033	4.00±0.1	6.80±0.1	1.5±0.1	4.0±0.1	8.0±0.1	16.0±0.3	3.4±0.1	1.75±0.1	0.35±0.05

Product Marking:


Marking	Printing (Inductance)
---------	-----------------------

Peel force of top cover tape:




The peel force of top cover tape shall be between 0.1 to 1.17 N

Reel Dimension: [mm]



Packaging Quantity:



Cautions and Warnings:

Storage Conditions:

- The storage period is within 12 months after the completion of production. Be sure to follow the storage conditions (temperature: -5 to 35°C, humidity: 75% RH Max). If the storage period elapses, the soldering of the terminal electrodes may deteriorate. The warranty period is one year.
- Product should not be exposed to environment with high temperature, high humidity, dust, corrosive gas and etc.
- Products should be handled with care to avoid damage or contamination from perspiration and skin oils.
- Please always handle products carefully to prevent any damage caused by dropping down or inappropriate removing.

Operation Instructions:

- Self heating (temperature increase) occurs when the power is turned ON, so the tolerance should be sufficient for the set thermal design.
- Before soldering, be sure to preheat components. The preheating temperature should be set so that the temperature difference between the solder temperature and chip temperature does not exceed 150°C.
-
-